Product datasheet Characteristics

11025

residual current circuit breaker - 2 poles - 40 A class AC 30 mA



Price*: 46.72 USD



Main

Range	Domae
Product or component type	Residual current circuit breaker (RCCB)
Device short name	RCCB
Poles description	2P
Earth-leakage protection class	Type AC

Complementary

9 9		
Main		
Range	Domae	
Product or component type	Residual current circuit breaker (RCCB)	
Device short name	RCCB	
Poles description	2P	
Earth-leakage protection class	Type AC	
Camplamentan		
Complementary Neutral position	Left	
	Outgoer	
Device location in system	40 A	
[In] rated current	AC	
Network type	50/60 Hz	
Network frequency		
[Ue] rated operational voltage	230 V AC 50/60 Hz conforming to IEC 61008	
Residual current tripping technology	Electromechanical	
Earth-leakage sensitivity	30 mA	
Earth-leakage protection time delay	Instantaneous	
Rated conditional short-circuit current	6 kA 40 A	
[Ui] rated insulation voltage	440 V	
[Uimp] rated impulse withstand voltage	4 kV	
Control type	Toggle	
Mounting mode	Fixed	
Mounting support	35 mm symmetrical DIN rail	
9 mm pitches	4	
Height	81 mm	
Width	36 mm	

^{*} Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

Depth	76 mm
Connections - terminals	Tunnel type terminals (downstream) 25 mm² flexible Tunnel type terminals (downstream) 35 mm² rigid Tunnel type terminals (upstream) 25 mm² flexible Tunnel type terminals (upstream) 35 mm² rigid

Environment

Standards	IEC 61008
Pollution degree	2
Tropicalisation	2 conforming to IEC 61008
Operating altitude	2000 m
Ambient air temperature for operation	-540 °C
Ambient air temperature for storage	-4060 °C

Packing Units

· doming orme		
Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	207 g	
Package 1 Height	3.8 cm	
Package 1 width	8.4 cm	
Package 1 Length	9.2 cm	
Unit Type of Package 2	BB1	
Number of Units in Package 2	6	
Package 2 Weight	1.322 kg	
Package 2 Height	9.5 cm	
Package 2 width	10 cm	
Package 2 Length	26 cm	
Unit Type of Package 3	S03	
Number of Units in Package 3	54	
Package 3 Weight	12.385 kg	
Package 3 Height	30 cm	
Package 3 width	30 cm	
Package 3 Length	40 cm	

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months