



⚠ Discontinued - Service only

## Commercial status

Discontinued on: 04 May 2021

End-of-service on: 22 September 2020

11026 has not been replaced. Please contact your customer care centre for more information.

## Main

Range	Domae
Product or component type	Residual current circuit breaker (RCCB)
Device short name	RCCB
Poles description	2P
Earth-leakage protection class	Type AC

## Complementary

Neutral position	Left
Device location in system	Outgoer
[In] rated current	40 A
Network type	AC
Network frequency	50/60 Hz
[Ue] rated operational voltage	230 V AC 50/60 Hz conforming to IEC 61008
Residual current tripping technology	Electromechanical
Earth-leakage sensitivity	300 mA
Earth-leakage protection time delay	Instantaneous
Rated conditional short-circuit current	6 kA 40 A
[Ui] rated insulation voltage	440 V
[Uimp] rated impulse withstand voltage	4 kV
Control type	Toggle
Mounting mode	Fixed
Mounting support	35 mm symmetrical DIN rail
9 mm pitches	4
Height	81 mm
Width	36 mm
Depth	76 mm
Connections - terminals	Tunnel type terminals (downstream) 25 mm <sup>2</sup> flexible

Tunnel type terminals (downstream) 35 mm<sup>2</sup> rigid  
 Tunnel type terminals (upstream) 25 mm<sup>2</sup> flexible  
 Tunnel type terminals (upstream) 35 mm<sup>2</sup> rigid

## Environment

Standards	IEC 61008
Pollution degree	2
Tropicalisation	2 conforming to IEC 61008
Operating altitude	2000 m
Ambient air temperature for operation	-5...40 °C
Ambient air temperature for storage	-40...60 °C

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	201 g
Package 1 Height	4 cm
Package 1 width	8.5 cm
Package 1 Length	9 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	6
Package 2 Weight	1.252 kg
Package 2 Height	10 cm
Package 2 width	9 cm
Package 2 Length	26 cm
Unit Type of Package 3	S03
Number of Units in Package 3	54
Package 3 Weight	11.755 kg
Package 3 Height	30 cm
Package 3 width	30 cm
Package 3 Length	40 cm

## Offer Sustainability

Sustainable offer status	Green Premium product
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

## Contractual warranty

Warranty	18 months
----------	-----------