



Price* : 75.00 USD



Main

| | |
|---|--|
| Range | ComPact |
| Product name | Compact INS |
| Product or component type | Switch disconnector |
| Poles description | 3P |
| Network type | DC AC |
| Network frequency | 50/60 Hz |
| [Ie] rated operational current | AC-22A: 40 A AC 50/60 Hz 220/240 V AC-22A: 40 A AC 50/60 Hz 380/415 V AC-22A: 40 A AC 50/60 Hz 440/480 V AC-22A: 40 A AC 50/60 Hz 500 V AC-23A: 32 A AC 50/60 Hz 500 V AC-23A: 40 A AC 50/60 Hz 220/240 V AC-23A: 40 A AC 50/60 Hz 380/415 V AC-23A: 40 A AC 50/60 Hz 440/480 V DC-22A: 40 A DC 125 V 2 poles in series DC-23A: 40 A DC 125 V 2 poles in series |
| [Ui] rated insulation voltage | 690 V AC 50/60 Hz |
| [Uimp] rated impulse withstand voltage | 8 kV |
| [Ith] conventional free air thermal current | 40 A at 60 °C |
| [Icm] rated short-circuit making capacity | 15 kA switch-disconnector alone 500 V AC at 50/60 Hz 75 kA with upstream protection circuit breaker 500 V AC at 50/60 Hz |
| [Ue] rated operational voltage | 125 V DC 500 V AC 50/60 Hz |
| Suitability for isolation | Yes |
| Contact position indicator | Yes |
| Visible break | No |
| Pollution degree | 3 |

* Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

Complementary

| | |
|--|--|
| Control type | Rotary handle |
| Handle colour | Black |
| Mounting mode | Fixed |
| Mounting support | DIN rail Plate |
| Upside connection | Front |
| Downside connection | Front |
| Cable cross section | 1.5...50 mm ² |
| Maximum power | AC-23: 11 kW at 220/240 V AC 50/60 Hz AC-23: 18.5 kW at 500/525 V AC 50/60 Hz AC-23: 20 kW at 380/415 V AC 50/60 Hz AC-23: 22 kW at 440 V AC 50/60 Hz |
| Rated duty | Uninterrupted |
| Intermittent duty class | Class 120 - 60 % |
| Enclosure dimensions for lthe | 190 mm x 115 mm x 55 mm |
| [Icw] rated short-time withstand current | 0.067 kA during 20 s conforming to IEC 60947-3 1.73 kA during 3 s conforming to IEC 60947-3 3 kA during 1 s conforming to IEC 60947-3 5.5 kA during 30 s conforming to IEC 60947-3 |
| Mechanical durability | 20000 cycles |
| Electrical durability | AC-22A: 1500 cycles 220/240 V AC 50/60 Hz AC-22A: 1500 cycles 380/415 V AC 50/60 Hz AC-22A: 1500 cycles 440 V AC 50/60 Hz AC-22A: 1500 cycles 500 V AC 50/60 Hz AC-23A: 1500 cycles 220/240 V AC 50/60 Hz AC-23A: 1500 cycles 380/415 V AC 50/60 Hz AC-23A: 1500 cycles 440 V AC 50/60 Hz AC-23A: 1500 cycles 500 V AC 50/60 Hz DC-22A: 1500 cycles 250 V DC 2 poles in series DC-23A: 1500 cycles 250 V DC 2 poles in series |
| Connection pitch | 18 mm |
| Height | 85 mm |
| Width | 90 mm |
| Depth | 62.5 mm |
| Net weight | 0.5 kg |

Environment

| | |
|---------------------------------------|------------------------------|
| Standards | IEC 60947-1 IEC 60947-3 |
| Product certifications | KEMA-KEUR CCC |
| IP degree of protection | IP40 conforming to IEC 60529 |
| IK degree of protection | IK07 conforming to EN 50102 |
| Ambient air temperature for operation | -25...70 °C |
| Ambient air temperature for storage | -50...85 °C |

Packing Units

| | |
|------------------------------|--------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 601 g |
| Package 1 Height | 0.2 cm |
| Package 1 width | 9.8 cm |
| Package 1 Length | 10 cm |
| Unit Type of Package 2 | S03 |
| Number of Units in Package 2 | 18 |

| | |
|------------------------------|------------|
| Package 2 Weight | 11.442 kg |
| Package 2 Height | 30 cm |
| Package 2 width | 30 cm |
| Package 2 Length | 40 cm |
| Unit Type of Package 3 | P12 |
| Number of Units in Package 3 | 144 |
| Package 3 Weight | 102.872 kg |
| Package 3 Height | 80 cm |
| Package 3 width | 80 cm |
| Package 3 Length | 120 cm |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| RECh Regulation | RECh Declaration |
| RECh free of SVHC | Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS declaration |
| Environmental Disclosure | Product Environmental Profile |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|