Product datasheet Characteristics

50441

Closed toroid for residual current protection SA - \varnothing 200 mm





Main

Range	Vigirex
Device short name	SA200
Product or component type	Earth leakage current sensor
Device application	Equipment monitoring and control
Current sensor type	A type closed toroid
[le] rated operational current	400 A

Complementary

1/1000	. <u></u>
DC	ite ite
AC	ep Le
45440 Hz	
100 kAfor 0.5 s	De US
85 kA / 0.5 s conforming to IEC 60947-2	substitute for and is not to be used for determining
1000 V	and
IV	te fo
12 kV	Dostiti
Fixed (cables) Fixed (plain backplate) Fixed (profiled sheet metal) Fixed (slotted backplate)	This documentation is not intended as a si
7.05 MJ	
Screw connection 0.22 mm²	ition———————————————————————————————————
196 mm inner:	en
100 mm for 2 cables : 185 mm² (maximum)	
1.32 kg	iTi o
256 mm	
	DC AC 45440 Hz 100 kAfor 0.5 s 85 kA / 0.5 s conforming to IEC 60947-2 1000 V IV 12 kV Fixed (cables) Fixed (plain backplate) Fixed (profiled sheet metal) Fixed (slotted backplate) 7.05 MJ Screw connection 0.22 mm² 196 mm inner: 100 mm for 2 cables : 185 mm² (maximum) 1.32 kg

Width	274 mm
Depth	46 mm

Environment

IP degree of protection	Connectors: IP20 IP30
Environmental characteristic	Exposure to damp heat not in service (2555 °C, RH 95 %) : 28 cycles conforming to IEC 60068-2-30 Salt mist: Kb/2 conforming to IEC 60068-2-52 Exposure to damp heat in service: category C2: 48 hours conforming to IEC 60068-2-56
Pollution degree	Level 3 conforming to IEC 60664-1
Ambient air temperature for operation	-3570 °C
Ambient air temperature for storage	-5585 °C

Packing Units

i acking critis	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	1.1 kg
Package 1 Height	7.5 cm
Package 1 width	27 cm
Package 1 Length	28.4 cm
Unit Type of Package 2	S04
Number of Units in Package 2	12
Package 2 Weight	13.966 kg
Package 2 Height	30 cm
Package 2 width	40 cm
Package 2 Length	60 cm
Unit Type of Package 3	P12
Number of Units in Package 3	48
Package 3 Weight	67.864 kg
Package 3 Height	80 cm
Package 3 width	80 cm
Package 3 Length	120 cm

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Compliant EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	End of Life Information	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	

Contractual warranty

Warranty	18 months