



## Commercial status



To be discontinued on: 15 December 2021

To be end-of-service on: 15 December 2021

⚠ To be discontinued

### Main

Range	Actassi
Product	Patch cord
Colour	Blue
Cable shielding type	UTP

### Complementary

Type of cable	4 pair cables
Rated voltage	150 V AC
[In] rated current	1.5 A
Insulation resistance	500 MOhm
Cable length (customisable value in configurator)	0...2 m
Communication network category	6
Contacts material	Phosphor bronze with 50 micro-inches gold over 100 micro-inches nickel
Contact resistance	10 mOhm
AWG	AWG 24
Attenuation	Guaranteed: 0.1 dB
Far end crosstalk [FEXT]	49.8 dB
Power sum far end crosstalk [PSFEXT]	46.9 dB
Minimum number of matings	1000 cycles
Targeted region	Asia Pacific.

### Environment

Flame retardance	CM
Standards	IEC 60603-7 FCC part 68 subpart F AS/NZS 3080:2003 TIA/EIA-568-B

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	105 g
Package 1 Height	1 cm
Package 1 width	21 cm
Package 1 Length	30.2 cm
Unit Type of Package 2	CAR
Number of Units in Package 2	90
Package 2 Weight	10.5 kg
Package 2 Height	42 cm
Package 2 width	62 cm
Package 2 Length	27 cm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

## Contractual warranty

Warranty	18 months
----------	-----------

## ACTPC6UBCM20BU is replaced by:



### Copper connectivity ACTPC6UUCM20BU

Patch cord, Actassi, Category 6, U/UTP, PVC, 2 m, blue

Qty 1