



Price* : 2,472.32 PHP



Main

Range of product	Actassi
Product or component type	Patch panel
Device presentation	Empty
Provided equipment	Without RJ45 connectors

Complementary

[In] rated current	1.5 A
Number of port	24 port of UTP
Product compatibility	standard 19" cabinet/rack
Communication network category	6 5e
Contact resistance	20 µOhm
Insulation resistance	>= 10 MOhm
Minimum number of matings	750 cycles
Number of rack unit	1U
Type of connector	S-110 keystone

Environment

Ambient air temperature for operation	-10...50 °C
Ambient air temperature for storage	-20...60 °C
Relative humidity	0...93 %
Standards	TIA/EIA-568-B

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

* List Price displayed is VAT EXCLUSIVE.

Package 1 Weight	816 g
Package 1 Height	5.2 cm
Package 1 width	12.5 cm
Package 1 Length	49.7 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile