



Commercial status

Discontinued on: 30 June 2020

End-of-service on: 20 January 2021

DCEKYSTU-WT has not been replaced. Please contact your customer care centre for more information.

 Discontinued

Main

Range of product	Digilink
Product or component type	Modular jack
Cable shielding type	UTP
Communication network category	5e
Colour tint	White

Complementary

Connector type	RJ45
Type of footprint	Keystone
Insulation resistance	≥ 500 mOhm at 500 V DC
Minimum number of matings	750 cycles
Contacts material	Phosphor bronze with 50 micro-inches gold over 100 micro-inches nickel
Pulling force	140 N
Delay skew	2.5 ns at 1...100 MHz
[In] rated current	1.5 A
Contact resistance	20 mOhm
[Ue] rated operational voltage	< 72 V DC

Environment

Flame retardance	V-0 conforming to UL 94
Product certifications	UL/ETL verified UL listed
Standards	ANSI/TIA-568-C.2 CENELEC EN 50173 ISO/IEC 11801 class E

Packing Units

Package 1 Weight	10.000 g
Package 1 Height	0.100 mm
Package 1 width	85.000 mm
Package 1 Length	150.000 mm

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
