



Main

Range of product	Digilink
Product or component type	Modular jack
Cable shielding type	UTP
Communication network category	6A
Colour tint	White

Complementary

Connector type	RJ45
Type of footprint	Keystone
Insulation resistance	≥ 500 mOhm at 500 V DC
Minimum number of matings	750 cycles
Contacts material	Phosphor bronze with 50 micro-inches gold over 100 micro-inches nickel
Pulling force	140 N
Delay skew	2.5 ns at 1...100 MHz
[In] rated current	1.5 A
Contact resistance	20 mOhm
[Ue] rated operational voltage	< 72 V DC

Environment

Flame retardance	V-0 conforming to UL 94
Product certifications	UL/ETL verified UL listed
Standards	CENELEC EN 50173 ANSI/TIA-568-C.2 ISO/IEC 11801 class E

Packing Units

Package 1 Weight	0.009 kg
Package 1 Height	1.000 cm
Package 1 width	9.000 cm

Package 1 Length	15.000 cm
------------------	-----------

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins