



Price* : 70.94 USD



Main

Range	Pieno
Product or component type	Power socket-outlet
Device application	Power supply
Switch function	Switch
Rated current	13 A at 250 V AC 50 Hz
Number of gangs	1 gang
Load type	No inductive load

Complementary

Wiring device mounting	Flush Surface
Outlet poles configuration	2P + E china
Material	Polycarbonate: surround Polycarbonate: grid plate
Connections - terminals	Switch: pillar terminals Socket: clamp terminal
Clamping connection capacity	2 x 2.5 mm ² for solid cable(s)
Width	87 mm
Height	87 mm
Depth	8.8 mm

Environment

Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
Standards	GB 16915.1-2003 GB 2099.1-2008

* Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile