# Product datasheet Characteristics

# **E8215USB\_WE**

13A 1 Gang Switched Socket with 2.1A USB, White



Price\*: 682.69 USD



### Main

Pieno
Power socket-outlet + USB charger
Mechanism
Shuttered
White
No inductive load

## Complementary

Complementary	
Socket number	1
Device mounting	Flush 47 mm
Switch function	ON/OFF power-socket outlet
Number of power socket outlets	1 x 2P + E with shutters, British
Rated current	Power circuit: 13 A 220250 V, AC, 50/60 Hz
Surface finish	Glossy
Surface treatment	Untreated
Number of gangs	1 gang
Connector type	USB type A
[Ue] rated operational voltage	220250 V AC 50/60 Hz
Maximum power consumption in W	0.075 W
Input power	16 W
Integrated connection type	2 USB port 5 V DC, maximum load current: 2.1 A
Material	Polycarbonate: grid plate Polycarbonate: cover Polycarbonate: surround Polycarbonate: dolly Nylon + GF: shutter Brass: contact plate

<sup>\*</sup> Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.



Steel: spring Nickel steel: terminal screw Protection type USB port: over temperature protection with PWM IC circuit USB port: over voltage protection against surges with PWM IC circuit USB port: overcurrent between output phases and earth (on power up only) with PWM IC circuit Shape of screw head Cross Screwdriver shape Philips Electrical connection 3 screw terminal Clamping connection capacity 1 x 4 mm<sup>2</sup> for solid cable(s) 2 x 4 mm<sup>2</sup> for stranded cable(s) 1 x 2.5 mm<sup>2</sup> 2 x 2.5 mm<sup>2</sup> Wire stripping length 10...12 mm Mounting support Mounting box conforming to BS 4662 Fixing mode By screws M3.5 x 25 mm Fixing center 60.3 mm Product compatibility Apple HW Power bank Tablet PC XiaoMi Smartphone Samsung HTC Height 87 mm Width 87 mm

#### Environment

Net weight

Embedding depth

Depth

<= 2000 m
040 °C
-560 °C
095 %
IEC 60950-1 BS 1363-2
IEC
IP20
Liquid soap Alcohol

42.15 mm

30.1 mm

0.1064 kg

# **Packing Units**

Package 1 Weight	106.000 g	
Package 1 Height	43.000 mm	
Package 1 width	87.000 mm	
Package 1 Length	87.000 mm	

#### Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes

China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information