



Main

| | |
|---------------------------|------------------------|
| Range | Pieno |
| Product or component type | Power socket-outlet |
| Switch function | Switch |
| Rated current | 15 A at 250 V AC 50 Hz |
| Number of gangs | 1 gang |
| Load type | Resistive |
| Cover frame colour tint | Wine gold |

Complementary

| | |
|------------------------------|--|
| Wiring device mounting | Flush Surface |
| Material | Polycarbonate: surround Polycarbonate: grid plate |
| Clamping connection capacity | 2 x 2.5 mm ² for solid cable(s) |
| Width | 87 mm |
| Height | 87 mm |
| Depth | 31.8 mm |

Environment

| | |
|---------------------------------------|-----------------------------|
| Ambient air temperature for operation | -5...40 °C |
| Relative humidity | 0...95 % |
| Standards | BS 546 MS 1577 SS 472 |

Packing Units

| | |
|------------------|----------|
| Package 1 Weight | 81.990 g |
|------------------|----------|

| | |
|------------------|-----------|
| Package 1 Height | 31.800 mm |
| Package 1 width | 87.000 mm |
| Package 1 Length | 87.000 mm |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure | Product Environmental Profile |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|