



Price* : 120.30 USD



Main

Range	Pieno
Product or component type	Power socket-outlet
Device application	Power supply
Switch function	Switch
Rated current	13 A at 250 V AC 50...60 Hz
Number of gangs	1 gang
Load type	Resistive
Cover frame colour tint	Aluminium silver

Complementary

Wiring device mounting	Surface Flush
Material	Polycarbonate: surround Polycarbonate: grid plate
Clamping connection capacity	2 x 4 mm ² for stranded cable(s) 3 x 2.5 mm ² for solid cable(s)
Width	87 mm
Height	87 mm
Depth	26.6 mm

Environment

Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
Standards	SS 145-2 MS 589-2 BS 1363-2

* Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

Packing Units

Package 1 Weight	73.940 g
Package 1 Height	27.200 mm
Package 1 width	87.000 mm
Package 1 Length	87.000 mm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile