



Main

Range	Pieno
Product or component type	Switch
Device application	Control
Switch application	Bell
Load type	Resistive
Cover frame colour tint	Aluminium silver

Complementary

Device mounting	Flush Surface
Wiring device mounting	Surface Flush
Switch function	Momentary
Rated current	10 A at 250 V AC 50 Hz
Local signalling	Fluorescent (white)
Number of gangs	1 gang
Material	Polycarbonate: surround Polycarbonate: grid plate
Connections - terminals	Pillar terminals
Clamping connection capacity	2 x 1.5 mm ² for stranded cable(s) 2 x 2.5 mm ² for solid cable(s)
Embedding depth	23 mm
Width	87 mm
Height	87 mm
Depth	23 mm

Environment

Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
Standards	SS 227-1 IEC 60669-1 MS IEC 60669-1 GB 16915.1 BS EN 60669-1

Packing Units

Package 1 Weight	73.770 g
Package 1 Height	35.700 mm
Package 1 width	87.000 mm
Package 1 Length	87.000 mm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile