



Price* : 467.85 USD



Main

Range	Pieno
Product or component type	Switch
Device application	Control
Switch application	Switch
Load type	Resistive Fluorescent
Cover frame colour tint	Wine gold

Complementary

Device mounting	Surface Flush
Wiring device mounting	Surface Flush
Rated current	45 A at 250 V AC 50 Hz
Local signalling	Neon
Number of gangs	1 gang
Material	Polycarbonate: surround Polycarbonate: grid plate
Connections - terminals	Pillar terminals
Clamping connection capacity	1 x 16 mm ² for solid cable(s) 1 x 10 mm ² for stranded cable(s)
Embedding depth	23 mm
Width	87 mm
Height	87 mm
Depth	33.8 mm

* Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

Environment

Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
Standards	GB 16915.1 BS EN 60669-1 SS 227-1 MS IEC 60669-1 IEC 60669-1

Packing Units

Package 1 Weight	144.200 g
Package 1 Height	35.500 mm
Package 1 width	87.000 mm
Package 1 Length	87.000 mm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile