



Price\* : 243.06 USD



### Main

Range	Pieno
Product or component type	Switch
Device application	Control
Switch application	Switch
Load type	Fluorescent Resistive
Cover frame colour tint	Matt black

### Complementary

Device mounting	Flush Surface
Wiring device mounting	Surface Flush
Switch function	Intermediate
Rated current	16 AX at 250 V AC 50 Hz
Local signalling	Fluorescent (white)
Number of gangs	1 gang
Material	Polycarbonate: surround Polycarbonate: grid plate
Connections - terminals	Pillar terminals
Clamping connection capacity	2 x 1.5 mm <sup>2</sup> for stranded cable(s) 2 x 2.5 mm <sup>2</sup> for solid cable(s)
Embedding depth	19.6 mm
Width	87 mm
Height	87 mm
Depth	19.6 mm

\* Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

## Environment

Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
Standards	SS 227-1 MS IEC 60669-1 GB 16915.1 BS EN 60669-1 IEC 60669-1

## Packing Units

Package 1 Weight	87.910 g
Package 1 Height	31.700 mm
Package 1 width	87.000 mm
Package 1 Length	87.000 mm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	<a href="#">Product Environmental Profile</a>