



Main

Range of product	Pieno
Product or component type	Switch
Switch function	1-way
Switch application	Switch
Rated current	10 AX at 250 V AC 50 Hz
Local signalling	Neon
Number of gangs	4 gangs
Load type	Fluorescent Resistive

Complementary

Wiring device mounting	Flush Surface
Material	Polycarbonate: surround Polycarbonate: grid plate
Connections - terminals	Pillar terminals
Clamping connection capacity	2 x 2.5 mm ² for solid cable(s) 3 x 1.5 mm ² for stranded cable(s)
Width	87 mm
Height	87 mm

Environment

Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
Standards	GB 16915.1 IEC 60669-1
Product certifications	CCC

Packing Units

Package 1 Weight	100.240 g
Package 1 Height	17.000 cm
Package 1 width	3.550 cm
Package 1 Length	11.600 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile