



Price\* : 67.75 USD



## Main

Product or component type	Push-button
Device application	Doorbell
Colour tint	White

## Complementary

Device presentation	Complete product
Rated current	10 A at 250 V AC 50/60 Hz
Number of gangs	1 gang
Number of rocker	1
Clamping connection capacity	3 x 2.5 mm <sup>2</sup> for solid cable(s) 3 x 2.5 mm <sup>2</sup> for stranded cable(s) 4 x 1.5 mm <sup>2</sup> for solid cable(s) 4 x 1.5 mm <sup>2</sup> for stranded cable(s)
Connections - terminals	Brass terminal
Material	Polycarbonate: grid plate Polycarbonate: base Polycarbonate: dolly Polycarbonate: frame Polycarbonate + GF 20 %: actuator
Marking	Bell symbol
Device mounting	Surface Flush
Width	86 mm
Height	86 mm
Depth	34.2 mm

\* Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

## Environment

IP degree of protection	IP20
Maximum ambient air temperature for operation	45 °C
Relative humidity	0...95 %
Operating altitude	2000 m
Environmental characteristic	UV resistant
Standards	MS IEC 60669-1 BS EN 60669-1 SS 227-1 IEC 60669-1

## Packing Units

Package 1 Weight	77.000 g
Package 1 Height	34.000 mm
Package 1 width	86.000 mm
Package 1 Length	86.000 mm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	<a href="#">Product Environmental Profile</a>