



⚠ Discontinued

Main

Range	Neo
Product or component type	Power socket-outlet
Device application	Power supply
Switch function	2-pole
Outlet poles configuration	3P with shutters
Outlet standard	BS 1363 MS 589 SS 145
Bulb type	LED, blue
Colour tint	Grey silver

Complementary

Wiring device mounting	Surface Flush
Rated current	13 A at 250 V AC 50/60 Hz
Material	Brass: contact Copper with silver onlay: bridge Nylon: shutter Polycarbonate: grid plate Polycarbonate: surround Steel with brass plating: screws Steel with brass plating: terminals
Load type	Resistive
Connections - terminals	Pillar terminals
Width	147 mm
Height	87 mm
Depth	18 mm

Environment

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Environmental characteristic	Indoor use
Standards	BS 1363 SS 145 MS 589

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile