# Product datasheet Characteristics

## EZ9D56832

Easy9 RCBO 240V - 1P + N - 32A - C curve - 6000 A - 30 mA



### Commercial status

Discontinued on: 02 April 2021

End-of-service on: 03 April 2021

EZ9D56832 has not been replaced. Please contact your

customer care centrefor more information.

#### Main

IVIAIII		
Range	Easy9	
Product or component type	Residual current breaker with overcurrent protection (RCBO)	
Device short name	Easy9 RCBO	
Poles	1P + Ns	
Neutral position	Left	
[In] rated current	32 A	
Earthing system	TN	
Network type	AC	
Trip unit technology	Thermal-magnetic	
Curve code	С	
Earth-leakage sensitivity	30 mA	
Earth-leakage protection time delay	Instantaneous	
Earth-leakage protection class	Type A	
Breaking capacity	6000 A Icn at 240 V AC 50 Hz conforming to BS EN 61009-1	

#### Complementary

Device application	Distribution
Device location in system	Outgoer
Network frequency	50 Hz
[Ue] rated operational voltage	240 V AC 50 Hz
Magnetic tripping limit	35 x ln
Residual current tripping technology	Voltage dependent functional earth
Limitation class	3
[Ui] rated insulation voltage	500 V
[Uimp] rated impulse withstand voltage	4 kV
Contact position indicator	Yes
Control type	Toggle
Mounting support	DIN rail
9 mm pitches	2
Height	110 mm
Width	18 mm

Depth	72 mm	
Net weight	180 g	
Colour	Grey (RAL 7035)	
Mechanical durability	10000 cycles	
Electrical durability	4000 cycles 240 V AC 50 Hz	
Connections - terminals	Tunnel type terminal (top) 25 mm² rigid Tunnel type terminal (bottom) 16 mm² rigid Tunnel type terminal (bottom) 16 mm² flexible Cable (top) 2 cable(s) flexible	
Tightening torque	2 N.m top or bottom	
Earth-leakage protection	Integrated	

## Environment

Standards	BS EN 61009-1
Product certifications	CE
Overvoltage category	IV
Tropicalisation	2
Relative humidity	95 % at 55 °C
Ambient air temperature for operation	-1560 °C
Ambient air temperature for storage	-4085 °C

## Packing Units

Package 1 Weight	211.000 g	
Package 1 Height	75.000 mm	
Package 1 width	95.000 mm	
Package 1 Length	18.000 mm	

## Offer Sustainability

REACh Regulation	REACh Declaration	
EU RoHS Directive	Compliant EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	