# Product datasheet Characteristics

# GGBL6022LS

Lisse - universal dimmer - 2 gangs - 2 way - LED - 100W



Range	Lisse	† 
Aesthetic name	White moulded	
Product or component type	Dimmer	
Device presentation	Complete product	io G
Load type	230 V AC LED lamp: 5100 W Incandescent lamp: 25100 W Halogen lamp: 25100 W	products for
Colour tint	White matt	
Quantity per set	Set of 1	t jo

#### Complementary

Device mounting	Wall mounted	<u>}</u>
Dimmer application	Inductive load Resistive load	inio ce
[Ue] rated operational voltage	230 V AC 50 Hz	
Number of gangs	2 gangs	
Material	Urea (carbamide)	
Connections - terminals	Screw terminals	
Fixing mode	By screws M3.5 x 25 mm	1
Type of packing	Bag	<u>.v</u>
Height	87 mm	Ç
Width	87 mm	######################################
Depth	43.6 mm	
Net weight	0.11 kg	, , , , , , , , , , , , , , , , , , ,
		<u>_</u>

#### Environment

Standards	BS EN 60669-2-1	_ <u>.</u>
IP degree of protection	IP20	_ ;

## Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	112 g	
Package 1 Height	4.4 cm	
Package 1 width	12.5 cm	
Package 1 Length	20 cm	

### Offer Sustainability

REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins