Product datasheet Characteristics

GLVD1G2W4

Exclusive - rotary dimmer - 1 gang - white



Commercial status

Discontinued on: 31 December 2017

End-of-service on: 31 December 2017

GLVD1G2W4 has not been replaced. Please contact your

customer care centre for more information.

Main

Main		
Product or component type	Rotary dimmer	
Quantity per set	Set of 1	
Device presentation	Complete product	
Load type	Low voltage halogen lamp with electronic transformer: 60400 VA Incandescent lamp	
Colour tint	White matt	
Complementary		
Device mounting	Wall mounted	
Dimmer application	Inductive load Resistive load	
[Ue] rated operational voltage	230 V AC 50 Hz	
Number of gangs	1 gang	
Connections - terminals	Screw terminals	
Fixing mode	By screws M3.5 x 30 mm	
Material	Urea (carbamide)	
Height	86 mm	
Width	86 mm	
Depth	17 mm	
Net weight	0.098 kg	
Environment		
Standards	BS FN 60669-2-1	
	BS EN 60669-2-1 IP20	
	BS EN 60669-2-1 IP20	
IP degree of protection		
IP degree of protection Packing Units		
IP degree of protection Packing Units Package 1 Weight	IP20	
Standards IP degree of protection Packing Units Package 1 Weight Package 1 Height Package 1 width	IP20 101.000 g	

Complementary

Complementary	
Device mounting	Wall mounted
Dimmer application	Inductive load
	Resistive load
[Ue] rated operational voltage	230 V AC 50 Hz
Number of gangs	1 gang
Connections - terminals	Screw terminals
Fixing mode	By screws M3.5 x 30 mm
Material	Urea (carbamide)
Height	86 mm
Width	86 mm
Depth	17 mm
Net weight	0.098 kg
-	

Environment

Standards	BS EN 60669-2-1	- <u>.</u>
IP degree of protection	IP20	0 5

Packing Units

Package 1 Weight	101.000 g
Package 1 Height	48.000 mm
Package 1 width	93.000 mm
Package 1 Length	93.000 mm

Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)	
	EU RoHS Declaration	
Contractual warranty		
Contractual warranty Warranty	18 months	