Product datasheet Characteristics

GU6422CSS

Ultimate Screwless dimmer switch 250W/VA, 2gang, 2way, main & LV, st.steel



п	١л	2	т	n

TTT-CALL		2.
Range of product	Ultimate	†
Range	Ultimate	2
Aesthetic name	Screwless flat plate	
Product or component type	Dimmer	
Device application	Control	
Load type	Incandescent lamp 230 V AC halogen lamp: 250 W	to the state of th
Colour tint	Stainless steel	
Quantity per set	Set of 1)

Complementary

Switch function	2-way	
Device mounting	Wall mounted	
Dimmer application	Resistive load Inductive load	de company
[Ue] rated operational voltage	230 V AC 50 Hz	
Number of gangs	2 gangs	
Connections - terminals	Screwless terminals	
Fixing mode	By screws M3.5 x 25 mm By screws M3.5 x 30 mm	. <u></u>
Height	88 mm	<u> </u>
Width	88 mm) :
Depth	25 mm	- <u>-</u>

Environment

Standards	BS EN 60669-2-1	not i
IP degree of protection	IP20	tion is

Packing Units

	000 000
Package 1 Weight	262.000 g

Package 1 Height	47.000 mm	
Package 1 width	90.000 mm	
Package 1 Length	103.000 mm	

Offer Sustainability

REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	