Product datasheet Characteristics

INS55300

Mita - 87 mm mounting plate - twin switched socket-outlet (DE/CE)



Range	Mita	:
Product or component type	Mounting plate	
Accessory / separate part category	Mounting accessory	
Type of floor	Raised floor	
Floor box shape	Rectangular	
Device presentation	Equipped	
Colour tint	Blue (RAL 5003)	
Quantity per set	Set of 1	

Complementary

Range	Mita	
Product or component type	Mounting plate	
Accessory / separate part category	Mounting accessory	
Type of floor	Raised floor	
Floor box shape	Rectangular	
Device presentation	Equipped	
Colour tint	Blue (RAL 5003)	
Quantity per set	Set of 1	
Complementary		
Range compatibility	mounting plate	
Product destination	3 compartments floor outlet box	
Socket-outlet type	Twin switched socket-outlet conforming to BS 1363 13 A dual earth and clean earth	
Material	Sheet steel PA (polyamide) 6	
Thickness	1.2 mm	
Length	173 mm	
Width	87 mm	
Depth	32 mm	
[In] rated current	13 A at 230 V AC	
Connections - terminals	Screw terminal	
For decision and		
Environment	IDOO	
IP degree of protection	IP20	
Ambient air temperature for operation	-2560 °C	
Packing Units		
Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	260 g	

Environment

ID decree of austration	ID20
IP degree of protection	IP20
Ambient air temperature for operation	-2560 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	260 g

Package 1 Height	3.2 cm	
Package 1 width	8.7 cm	
Package 1 Length	17.3 cm	

Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	