



Price\* : 78.76 USD



### Main

Range	Vivace
Device short name	KB30
Product or component type	Fuse connection unit
Device presentation	Complete mechanism

### Complementary

Colour tint	White
Material	Polycarbonate: grid plate Polycarbonate: surround Polycarbonate: base
Projecting depth	8 mm
Device mounting	Surface
Mounting support	Wall mounted
Fixing mode	By screw M3.5
Fixing center	60.3 mm
Embedding depth	35 mm
Rated current	13 A at 250 V AC, resistive
Network frequency	50 Hz
Contacts material	Brass and phosphor bronze
Connections - terminals	Pillar terminal
Terminal identifier	L out N out L in N in Earth
Tightening torque	0.4 N.m
Clamping connection capacity	2 x 4 mm <sup>2</sup> incoming 3 x 2.5 mm <sup>2</sup> incoming 1 x 1.5 mm <sup>2</sup> outgoing

\* Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

	1 x 2.5 mm <sup>2</sup> input
Width	87 mm
Height	87 mm

## Environment

Standards	BS 1363-4
Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
Environmental characteristic	Indoor use

## Packing Units

Package 1 Weight	88.200 g
Package 1 Height	86.000 mm
Package 1 width	35.000 mm
Package 1 Length	146.000 mm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

## Contractual warranty

Warranty	18 months
----------	-----------