## **Product datasheet** Characteristics

# KB32TV 2 Gang TV Coaxial Outlet





#### Main

Range of product	Vivace	
Range	Vivace	
Device short name	KB32	
Product or component type	TV socket	
Device presentation	Complete mechanism	

## Complementary

<i>l</i> lain		
Range of product	Vivace	
Range	Vivace	
Device short name	KB32	
Product or component type	TV socket	
Device presentation	Complete mechanism	
Complementary		
Number of gangs	1 gang	
Number of outputs	2	
Colour tint	White	
Material	Polycarbonate: surround Polycarbonate: grid plate Polycarbonate: base	
Projecting depth	8 mm	
Device mounting	Flush	
Mounting support	Wall mounted	
ixing mode	By screw M3.5	
ixing center	60.3 mm	
Embedding depth	35 mm	
Fightening torque	0.4 N.m	
Vidth	86 mm	
Height	86 mm	
Environment		
Ambient air temperature for operation	-540 °C	
Relative humidity	095 %	
	Indoor use	

#### Environment

Ambient air temperature for operation	-540 °C
Relative humidity	095 %
Environmental characteristic	Indoor use

## Packing Units

Package 1 Weight	67.800 g	
Package 1 Height	86.000 mm	
Package 1 width	50.000 mm	
Package 1 Length	86.000 mm	

## Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Compliant EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information	
Environmental Disclosure	vironmental Disclosure Product Environmental Profile	

#### Contractual warranty

Warranty	18 months	