



Price* : 330.74 USD



Main

Range	Vivace
Product or component type	Switch
Device short name	KBT31
Device application	Lighting
Device presentation	Complete mechanism

Complementary

Switch function	Double 1-way vertical
Actuator	Rocker
Pilot light	Neon indicator lamp
Number of gangs	2 gangs
Colour tint	White
Material	Polycarbonate: grid plate Polycarbonate: surround Polycarbonate: base
Projecting depth	8 mm
Device mounting	Flush
Mounting support	Wall mounted
Fixing mode	By screw M3.5
Fixing center	120.6 mm
Embedding depth	47 mm
Rated current	45 A at 250 V AC, inductive 45 A at 250 V AC, resistive
[Ue] rated operational voltage	250 V AC
Network frequency	50 Hz
Contacts material	Brass and phosphor bronze

* Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

Connections - terminals	pillar terminal
Tightening torque	0.4 N.m
Clamping connection capacity	16 mm ²
Width	86 mm
Height	146 mm

Environment

Standards	MS IEC 60669-1 SS 227
Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
Environmental characteristic	Indoor use

Packing Units

Package 1 Weight	142.910 g
Package 1 Height	3.700 mm
Package 1 width	8.700 mm
Package 1 Length	14.700 mm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------