



Price* : 209.37 USD



Main

Range of product	Unica
Device application	Power supply
Product or component type	Switched socket
Device presentation	Mechanism with fixing frame
Outlet poles configuration	2 x 2P + E
Outlet standard	European

Complementary

Device mounting	Flush
Mounting support	Wall mounted
Pilot light	Red neon indicator
Rated current	13 A 250 V AC 50 Hz
Load type	Resistive
Number of gangs	1 gang
Fixing mode	By screw M3.5
Fixing center	60.3 mm
Colour tint	Graphite
Contacts material	Brass and phosphor bronze
Connections - terminals	Pillar terminal
Terminal identifier	L N Earth
Tightening torque	0.4 N.m
Clamping connection capacity	2 x 4 mm ² for rigid cable(s) 2 x 4 mm ² for stranded cable(s) 2 x 4 mm ² for flexible cable(s) 3 x 2.5 mm ² for rigid cable(s)

* Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

	3 x 2.5 mm ² for stranded cable(s) 3 x 2.5 mm ² for flexible cable(s)
Material	PC (polycarbonate): grid plate PP (polypropylene): base
Projecting depth	8 mm
Quantity per set	10 polybag
Embedding depth	35 mm
Depth	15 mm
Width	81 mm
Height	83 mm
Net weight	0.063 kg

Environment

Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
Operating altitude	<= 2000 m
IK degree of protection	IK01
IP degree of protection	IP20
Standards	SASO 2203 BS 7671 BS 1363
Environmental characteristic	Indoor use

Packing Units

Package 1 Weight	63.000 g
Package 1 Height	28.000 mm
Package 1 width	117.000 mm
Package 1 Length	160.000 mm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile