



### Main

|                           |                             |
|---------------------------|-----------------------------|
| Range of product          | Unica                       |
| Device application        | Control                     |
| Product or component type | Switch                      |
| Device presentation       | Mechanism with fixing frame |
| Colour tint               | Graphite                    |

### Complementary

|                         |   |
|-------------------------|---|
| Switch function         | 2-way   |
| Device mounting         | Flush   |
| Mounting support        | Wall mounted  |
| Fixing center           | 60.3 mm   |
| Rated current           | 16 AX at 250 V AC, inductive<br>16 AX at 250 V AC, fluorescent  |
| Load type               | Load for energy saving lamps with ballast: 200 W  |
| Network frequency       | 50 Hz   |
| Contacts material       | Brass and phosphor bronze   |
| Actuator                | Rocker  |
| Number of gangs         | 1 gang  |
| Fixing mode             | By screw M3.5   |
| Connections - terminals | Pillar terminal   |
| Terminal identifier     | L2<br>COM<br>L1   |
| Cable cross section     | 2.5 mm <sup>2</sup> rigid cable<br>2.5 mm <sup>2</sup> stranded cable<br>2.5 mm <sup>2</sup> flexible cable |
| Tightening torque       | 0.4 N.m   |
| Material                | PC + ASA: rocker  |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.

Polycarbonate: cover frame  
PA (polyamide) 6.6: base

|                 |          |
|-----------------|----------|
| Embedding depth | 35 mm    |
| Width           | 81 mm    |
| Height          | 83 mm    |
| Net weight      | 0.036 kg |

## Environment

|                                       |                        |
|---------------------------------------|------------------------|
| Ambient air temperature for operation | -5...40 °C             |
| Relative humidity                     | 0...95 %               |
| IK degree of protection               | IK01                   |
| IP degree of protection               | IP20                   |
| Standards                             | IEC 60669-1<br>BS 7671 |
| Environmental characteristic          | Indoor use             |

## Packing Units

|                  |            |
|------------------|------------|
| Package 1 Weight | 33.000 g   |
| Package 1 Height | 32.000 mm  |
| Package 1 width  | 117.000 mm |
| Package 1 Length | 160.000 mm |

## Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product   |
| REACH Regulation           | <a href="#">REACH Declaration</a>   |
| REACH free of SVHC         | Yes   |
| EU RoHS Directive          | Compliant<br><a href="#">EU RoHS Declaration</a>  |
| Toxic heavy metal free     | Yes   |
| Mercury free               | Yes   |
| RoHS exemption information | <a href="#">Yes</a>   |
| China RoHS Regulation      | <a href="#">China RoHS declaration</a><br>Pro-active China RoHS declaration (out of China RoHS legal scope) |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>   |