



Main

Range	ARGUS
Product or component type	Occupancy sensor
Device application	Lighting
Load type	Halogen lamp <= 1000 VA Energy saving lamp <= 80 VA Incandescent lamp <= 2000 W Low voltage halogen lamp <= 1000 VA Fluorescent lamp 100 µF <= 900 VA

Complementary

Rated voltage	230 V +/- 10 % AC 50/60 Hz
Detection angle	360°
Presence detection area	PIR: 360°, 7 m
Device mounting	Surface
Mounting support	Ceiling
Mounting height	2...3 m
Diameter	121.5 mm
Depth	42.5 mm

Environment

Electrical shock protection class	Class II
IP degree of protection	IP40
Ambient air temperature for operation	0...45 °C
Standards	EN 60669-1 EN 60669-2-1

Packing Units

Package 1 Weight	0.280 kg
Package 1 Height	1.000 cm
Package 1 width	1.000 cm
Package 1 Length	1.000 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information