Product datasheet Characteristics

VDIB17766UWE_E

Actassi - modular jack - category 6 - UTP - white - non shuttered





Main

TTT COLUMN		
Range	Actassi	
Product brand	Schneider Electric	-
Product type	Keystone modular jack	
Provided equipment	Without shutter	;
Colour tint	White	
Wiring Colour configuration	TIA-568A/B	
Type of packing	Plastic bag and carton	
Quantity per set	Set of 1	

Complementary

[In] rated current	1.5 A at 25 °C
Voltage proof	1000 V AC/DC peak, between contacts
Contact resistance	20 mOhm
Insulation resistance	>= 500 MOhm
Connector type	RJ45
AWG gauge	AWG 24AWG 22
Durability	1000 cycles
Tool type	Punch down tool Quick termination tool
Cable outer diameter	0.71.4 mm
Compatible LAN cable types	UTP
Communication network category	6
Supported applications	1000BASE-T
Product compatibility	RJ45 plug
Type of footprint	S-110 keystone
Targeted region	Asia Pacific.

Environment

Operational temperature range	-1060 °C
Ambient air temperature for storage	-2070 °C
Climatic category	40/070/21 (21 days)
Flame retardance	UL94-V0 conforming to UL listed
Product certifications	FCC part 68 F IEC 60603-7
Standards	IEC 11801 class E

Packing Units

Package 1 Weight	9.000 g	
Package 1 Height	0.200 mm	
Package 1 width	85.000 mm	
Package 1 Length	150.000 mm	

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)	
Environmental Disclosure	Product Environmental Profile	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	

Contractual warranty

Warranty	18 months